



REELS

Type	D1 mm	D2 mm	D3 mm	D4 mm	L1 mm	L2 mm	Tare g	CAPACITY (max)	
								Single End kg	Strand/Rope kg
WW 16C	67	34	16	28	72	82	72	0,8	-
WW 24C	67	34	16	28	107	117	92	1,2	-
HK 76/45 (biconical)	63	45	16	24	60	86	70	0,4	-
Din 63	63	40	11	15	49	63	40	0,4	-
DIN 80	80	50	16	24	64	80	125	1	-
Din 100	100	63	16	24	80	100	125	2	-
Din 125	125	80	16	24	100	125	200	4	-
Din 125/45 (biconical)	125	80	16	24	100	125	200	4	-
Din 160	160	100	22	34	128	160	350	9	8
Din 200/22	200	125	22	34	160	200	600	16	14
Din 250/36	250	160	36	44	160	200	1050	25	22
Din 355	355	224	36	60	160	200	1850	45	40
VM 400/36	400	250	36	-	250	290	2180	80	75
VM 400/127	400	250	127	-	250	290	2180	80	75
GMV 500/36	500	250	36	-	255	310	9525	220	210
GMV 500/127	500	250	127	-	255	310	8845	220	210
TF 630	630	315	127	-	315	375	62500	350	350

FSP-one also deliver on other kind of spools. Even on yours. Contact us for more information.

