

Soft Silver Plated High Strength Copper Alloy Green8® Stranded Wire

Standard	Material	ASTM B624
	Plating	ASTM B298
	Stranding	AS29606A

AWG	Construction	Cross-Sec. Area	Single Wire Diameter	Stranded Wire Diameter		Linear Weight	Electrical Resistance	Breaking Strength
		Nominal <i>Circular Mils</i>	Nominal <i>inch</i>	Min <i>inch</i>	Max <i>inch</i>	Nominal <i>lbs/1000ft</i>	Max <i>Ω/1000ft</i>	Min <i>lbs</i>
30	7/38	112	0.0040	0.0115	0.0124	0.343	117.4	5.2
28	7/36	175	0.0050	0.0135	0.0154	0.538	74.4	8.2
26	19/38	304	0.0040	0.0175	0.0194	0.941	44.8	14.2
24	19/36	475	0.0050	0.0225	0.0244	1.458	28.4	22.4
22	19/34	754	0.0063	0.0285	0.0304	2.352	17.5	35.8
20	19/32	1216	0.0080	0.0365	0.0395	3.763	10.7	58.1
18	19/30	1900	0.0100	0.0465	0.0477	5.846	6.43	90.3
16	19/29	2426	0.0113	0.0515	0.0538	7.459	4.9	115.0

Those values are obtained with a minimum elongation of 6%

Packaging	Spools	DIN250 to DIN355 - To be agreed
	Labelling	Product designation (customer) - Size Date - Part Nr (customer) - PO Number (customer) - Gross weight - Tara - Net Weight - Batch Number

- Our products are clear of imperfections and consistent with best industrial practices to **limit the amount of contaminants, dust and lubricants** during the manufacturing and packaging process.
- **Free certificate of compliance, or test report** with required and obtained values are available upon request.
- The data provided here have been established to the best of our knowledge and is for **informative purpose only**.
- Green8® product are **RoHS & REACH compliant**.